

Model Number	Power						Feedback			Servo Drive Mode						
	Voltage (V)		Rated (kW)		Current (A)		Iso Gnd	Hall	Enc	Tach	Torque	Duty Cycle	Voltage	IR Comp	Hall Vel	Vel
	AC	DC	Peak	Cont.	Peak	Cont.										
< sort >																
12A8	-	20 - 80	0.9	0.5	12	6			✓	✓		✓	✓			✓
25A8	-	20 - 80	1.9	1	25	12.5			✓	✓		✓	✓			✓
30A8	-	20 - 80	2.3	1.1	30	15			✓	✓		✓	✓			✓
20A20	-	40 - 190	3.6	1.8	20	10			✓	✓		✓	✓			✓
50A8	-	20 - 80	3.8	1.9	50	25			✓	✓		✓	✓			✓
120A10	-	20 - 80	9.1	4.6	120	60	✓		✓	✓		✓	✓			✓
100A40	-	80 - 400	38	19	100	50	✓		✓	✓		✓	✓			✓
BE15A8	-	20 - 80	1.1	0.6	15	7.5		✓	✓		✓	✓				✓
B15A8	-	20 - 80	1.1	0.6	15	7.5		✓			✓	✓				✓
BE30A8	-	20 - 80	2.3	1.1	30	15		✓	✓		✓	✓				✓
B30A8	-	20 - 80	2.3	1.1	30	15		✓			✓	✓			✓	✓
BE25A20	-	40 - 190	4.5	2.3	25	12.5		✓	✓		✓	✓				✓
BE25A20AC	30 - 125	40 - 190	4.5	2.3	25	12.5	✓	✓	✓		✓	✓				✓
B25A20	-	40 - 190	4.5	2.3	25	12.5		✓			✓	✓			✓	✓
B25A20AC	30 - 125	40 - 190	4.5	2.3	25	12.5	✓	✓			✓	✓			✓	✓
B30A40	-	60 - 400	11.4	5.7	30	15	✓	✓	✓		✓	✓			✓	✓
B30A40AC	45 - 265	60 - 400	11.4	5.7	30	15	✓	✓	✓		✓	✓			✓	✓
B40A40AC	45 - 265	60 - 400	15.2	7.6	40	20	✓	✓	✓		✓	✓			✓	✓
B40A40	-	60 - 400	15.2	7.6	40	20	✓	✓	✓		✓	✓			✓	✓
B060A400AC	200 - 240	255 - 373	21.3	10.6	60	30	✓	✓	✓		✓	✓	✓	✓	✓	✓
B100A400AC	200 - 240	255 - 373	35.4	17.7	100	50	✓	✓	✓		✓	✓	✓	✓	✓	✓

Model Number	Power						Feedback			Servo Drive Mode						
	Voltage (V)		Rated (kW)		Current (A)		Iso Gnd	Hall	Enc	Tach	Torque	Duty Cycle	Voltage	IR Comp	Hall Vel	Vel
	AC	DC	Peak	Cont.	Peak	Cont.										
< sort >																
S100A40	-	60 - 400	38	19	100	50				None			120° Sine			
S16A8	-	20 - 80	1.2	0.6	16	8				None			120° Sine			
S30A40	-	60 - 400	11.4	5.7	30	15				None			120° Sine			
S30A40AC	45 - 270	60 - 380	10.8	5.4	30	15				None			120° Sine			
S60A40	-	60 - 400	22.8	11.4	60	30				None			120° Sine			
S60A40AC	45 - 270	60 - 380	21.7	10.8	60	30				None			120° Sine			
SX25A20	-	60 - 190	4.5	2.3	25	12.5				None			120° Sine			